

## XL-620/XL-660

### Blackboard Speaker/Whiteboard Speaker

#### DESCRIPTION

1. Designed for electronic whiteboards, it has the characteristics of convenient installation and accurate vocal expression.
2. One way microphone input (environmental microphone jack comes with DC+6V power supply).
3. One stereo RCA input, one stereo RCA line output.
4. MP3 playback function, support high-speed USB2.0, SD / MMC / XD / MS card and other media, can achieve software upgrades.
5. Switchable AM/FM digital tuner.
6. With IR / infrared remote control, you can control the volume level / up and down / mute, automatically search for available stations, etc.
7. One-way dedicated USB microphone interface, using USB interface to support 2.4G microphone connection, can be extended to realize 2.4G microphone use at any time.
8. Standard wall mounting accessories, lifting is simple and convenient.



#### PARAMETERS

Model	XL-620	XL-660
Rated Power	60W	30W
Rated Impedance	4Ω	
Frequency Response	68Hz-18KHz	
Driver	4-inch Bass * 2, Treble * 1	4-inch Bass * 1, Treble * 1
Rated Input Level	Microphone 15mV (Unbalanced)	
Input	1 Microphone Input Interface, 1 Stereo Input	1 Channel Microphone Input Interface, 1 Set Of Stereo Input
Sensitivity	<500MV	
Signal To Noise Ratio	85dB	
The Maximum Sound Pressure Level	78dB	
Resolution	≥ 40dB	
Box Type	Inverted Phase	
Box And Exterior	High-density MDF (Black) Box, Steel Mesh	High-density MDF (White) Box, Steel Mesh
Installation	Standard Wall Mount	
Box Size (L * W * H)(mm)	150 * 84 * 700	
Net Weight(kg)	7.5	6.5